

EXCLUSIVELY FROM



The 4100T Overhead (Rotary Arm) Semi-Automatic Series

Choose a frame that fits your production situation.



4100-T-WM (Wall Mount)
4100-T-PM (Post Mount)



4100-T-FS3
Free-Standing 3 Post Stand



4100-T-FSU
Free-Standing "U" Shape Stand



4100H-FS
Free-Standing 4 Post Stand



4100-T-FSR
Rear Lag Down to Floor

- ❖ Affordable and simple with more standard features than any other overhead (rotary arm) pallet wrapper.
- ❖ A quality machine built with quality components And supported by a local qualified distributor.

We invite you to go online at www.cousinpackaging.com for more information or call your local distributor.

1 888 209 4344

4100-T & 4100-H DESIGN FEATURES/SPECIFICATIONS

LOAD CAPACITY:

- ❖ Unlimited load weight
- ❖ **4100-T:** 50" L x 50" W x 86" H max load size
- ❖ **4100-H:** 56" L x 56" W x 80" H max load size
- ❖ NOTE: Larger load size options are available

CONTROLS:

- ❖ Panasonic PLC
- ❖ Separate UP/DOWN Spiral Speed Controls
- ❖ Emergency Stop button
- ❖ Up Only or Up/Down wrap program
- ❖ Film tension (Force-to-Load) control
- ❖ Rotary arm and film carriage elevator dynamic braking
- ❖ Triple beam type auto load height sensing photo-eye, detects dark or shiny loads
- ❖ Separate 1 to 9 revolution top & bottom wrap control
- ❖ NEMA 12 control panel enclosure
- ❖ 115 Volts 1 Phase 60 Hz 15 Amps
- ❖ **3 Year Warranty on Components**

FILM CARRIAGE:

- ❖ Super Rapid Thread II™ 20" capacity pre-stretch film carriage
- ❖ Safety Door with auto power cut-off switch
- ❖ Special Film Threading Device – Uniquely orientates the sticky side of the film against the pre-stretch rollers **and** the inside on the load.
- ❖ 1/2 HP DC variable speed motor
- ❖ 33% to 313% fixed stretch capability
- ❖ Carriage Descent Safety Shut-Off Device
- ❖ Superior film-to-roller contact area
- ❖ **Lifetime warranty on pre-stretch rollers**

ARM/TOWER DESIGN:

- ❖ **4100-T:**
 - Double flange bearing support system
 - Twin V-belt drive pulleys with belt tensioner
 - 1-12 RPM rotational speed c/w soft start acceleration
 - 1/2 HP DC variable speed motor
- ❖ **4100-H:**
 - Heavy duty ring bearing – chain/sprocket drive
 - 1 – 15 RPM
 - 3/4 HP DC variable speed motor
- ❖ Dust tight slip ring assembly
- ❖ Final revolution deceleration and positive stop alignment
- ❖ Heavy Duty Structural Steel
- ❖ Electro-static powder coated paint finish
- ❖ **5 Year Warranty on Steel Fabrications**



4100-T control panel



4100-H control panel

